

# X5S

5MP PoE NVR with HDMI/VGA Output



## Specifications

Model		CS-X5S-4P	CS-X5S-8P
Network Parameter	PoE channels	4	8
	Uplink Port	1FE	1GE
	PoE Protocol	802.3af	802.3af
	Standard Power Supply Distance	100m	100m
	Maximum Power Supply Distance (UTP)	250m	250m
	Wired Access Bandwidth	40mbps	100mbps
Video Output	VGA	1 Channel, resolution: 1920*1080/60Hz、 1600*1200/60Hz、 1280*1024/60Hz、 1280*720/60Hz、 1024*768/60Hz	1 channel, resolution: 1920*1080/60Hz、 1600*1200/60Hz、 1280*1024/60Hz、 1280*720/60Hz、 1024*768/60Hz
	HDMI	1 Channel, resolution: 1920*1080/60Hz、 1600*1200/60Hz、 1280*1024/60Hz、 1280*720/60Hz、 1024*768/60Hz	1 Channel, resolution: 1920*1080/60Hz、 1600*1200/60Hz、 1280*1024/60Hz、 1280*720/60Hz、 1024*768/60Hz
	Audio Output	1, RCA interface ( Impedance: 1kΩ)	1, RCA interface ( Impedance: 1kΩ)

<b>Audio/Video Codec</b>	<b>Play Back Number</b>	4 channels , (1080p/20fps or 5MP low frame rate)	8 channels , 4 (1080p/15fps) or 4/8(5MP low frame rate)
	<b>Recording Resolution</b>	5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/2CIF/CIF/QCIF	5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/2CIF/CIF/QCIF
	<b>Video Compression</b>	H.265/H.264	H.265/H.264
	<b>Decode Playback</b>	Support 4*1080P	Support 8*1080P
<b>Video Record Management</b>	<b>Video Capture</b>	Manual video recording; dynamic detection video; regular video recording; alarm recording	Manual video recording; dynamic detection video; regular video recording; alarm recording
	<b>Backup Mode</b>	Support hard disk backup, Internet application backup	Support hard disk backup, Internet application backup
<b>HDD</b>	<b>Type</b>	One Built-in sata port	One Built-in sata port
	<b>Capability</b>	Support 1TB to 8TB 3.5inch HDD	Support 1TB to 8TB 3.5inch HDD
<b>External Interface</b>	<b>Audio Output</b>	Support	Support
	<b>Hardware Reset</b>	Support	Support
	<b>USB2.0 Interface</b>	2	2
<b>Power Consumption</b>	<b>Standby</b>	≤6W	≤6W
<b>Dimensions (mm)</b>	<b>length x width x high (mm)</b>	235x 270x44.5mm	235x 270x44.5mm
<b>Weight</b>	<b>Net Weight</b>	900g	900g