



- Color 1.3MP CMOS night vision camera
- 7" color TFT-LCD capacitive touch screen
- Support monitoring, video talk, unlock function
- 6ch alarm input, 1ch alarm output
- 32ch IP camera surveillance
- SD card pluggable, support record and snapshot
- Support network signal & power by 2 wires

Packaging




Technical Specifications

DHI-VTO2000A-2		
System	Main Processor	Embedded micro processor
	Operation System	Embedded LINUX OS
Video	Compression	H.264


	Input/Approaching Induction	1.3 megapixel CMOS camera	
	Night Vision	Support	
Audio	Audio Input	Microphone	
	Audio Output	Built-in speaker	
	Bidirectional Talk	Support bidirectional talk	
Operation Model	Input	One-key input	
	Door lock status check	Support (optional)	
Alarm	Vandal proof	Support	
Connection	2-wire		
Network	Ethernet	10M/100Mbps Self-adaptive	
	Network Protocol	TCP/IP	
General	Power	DC 24V	
	Power Consumption	Standby $\leq 1W$, work $\leq 7W$	
	work environment	-40°C~+60°C	
		Humidity: 10~95%RH	
	Water Proof	IP 54	
	Dimensions	129.9mm×32.2mm×140mm(L*W*T)	
	Weight	0.8 Kg	
Installation Method	Surface mounted		
DHI-VTH1550CH-2			
System	Main Processor	Built-in microcontroller	
	Operation System	Embedded LINUX operating system	
Video	compression	H.264	
	Resolution	800*480	
Audio	Audio Input	All-direction microphone	
	Audio Output	Embedded loudspeaker	
	Bidirectional Talk	Support bidirectional talk	
Display	Size	Color 7-inch TFT LCD	
Operating modes	input	Mechanical keys, Touch screen technology	
Alarm	Alarm input	Support 6 channels input	
	Alarm output	Support 1 channel input	

Connection	2-wire	
Network	Ethernet	10 M / 100 Mbps adaptive
	network protocol	TCP/IP
General	Power	DC 24V
	Power Consumption	Standby $\leq 1.5W$, work $\leq 7W$
	work environment	Temperature: $-10^{\circ}C \sim +60^{\circ}C$
		Humidity: 10~90%RH
	Dimensions	200mm \times 136mm \times 22mm(L*W*T);
	Weight	0.8Kg
	Installation Method	Surface mounted
DHI-VTNC3000A		
General	Voltage	DC 24V
	Channels	4
	Power Consumption	Standby: 1W(under free load)
		Max: 40W(under full load)
	work environment	$-10^{\circ}C \sim +55^{\circ}C$
	Dimensions	108mm*108mm*64mm(L*W*T)
	Weight	0.5 Kg;
Installation Method	Surface mounted & DIN-Rail Mounted	

System Diagram



Dimension Figure



Dahua Technology Co., Ltd.

1199BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Email: overseas@dahuatech.com

www.dahuatech.com