

THE SOFT REMORTE

Datasheet

nODon



The Soft Remote can directly control any kind of Z-Wave® or Z-Wave Plus® compliant devices such as NodOn® Smart Plug or trig scenes through a Z-Wave® or Z-Wave Plus® Home Automation Gateway.

TECHNICAL DATA

Power supply: CR2032 battery – 1.5 to 2 years lifetime

4 buttons

Embedded magnet for metallic surface sticking

Spill and shock resistant

Operational temperature – 0°C to 40°C - Altitude – 2.000m

Radio protocol Z-Wave®: 868.4MHz – 500 Series – Compliant Z-Wave Plus® SDK 06.51.06

Range: 40m indoor / 80m outdoor

Dimensions: 56*56*20mm

Warranty 2 years

STANDARDS

EN 60950-1:2006 + A11:2009 + A1:2010 + EN301 489-1 V1.9.2

A12:2011 + A2:2013

EN301 489-3 V1.6.1

EN 300 220-2 V2.4.1

EN 62479:2010

REFERENCES NUMBERS

CRC-3-6-01 - EAN : 3700313920237 – Cozy White

CRC-3-6-02 - EAN : 3700313920244 – Tech Blue

CRC-3-6-03 - EAN : 3700313920251 – Cozy Grey

CRC-3-6-04 - EAN : 3700313920336 – Wasabi

CRC-3-6-05 - EAN : 3700313920343 – Softberry

CRC-3-6-06 - EAN : 3700313920350 – Lagoon